

TECHNICAL SPECIFICATION 2025

DISCOVERY
SPORT



ENGINES AND TECHNICAL SPECIFICATION

Discovery Sport features advanced engine options, providing new levels of performance, efficiency, and refinement. There is a plug-in electric hybrid (PHEV) engine for all-electric, zero tailpipe emissions driving, as well as petrol and diesel options.

1

ENGINES

View the available engines, their fuel economy and specifications.

2

DIMENSIONS AND CAPABILITIES

View the ride height, turning circle and other capability specifications.

Engines

ENGINE			PETROL PLUG-IN ELECTRIC HYBRID (PHEV)		
ENGINE			P270e		
Plug-in Hybrid Electric Vehicle (PHEV)			■		
Transmission			Automatic		
Driveline			All Wheel Drive (AWD)		
Maximum power (PS / kW / rpm)			269* / 198* / 5.000-5.500		
Maximum torque (Nm / rpm)			540* / 2.000 - 3.250*		
Capacity (cc)			1.498		
No. of cylinders / Valves per cylinder			3 / 4		
Cylinder layout			Inline		
Bore / stroke (mm)			83,0 / 92,3		
Compression ratio (:1)			10,5+ / -0,5		
FUEL ECONOMY – WLTP**					
Seating			5		
WLTP Consumption	Combined	l/100km	3,9-4,2		
WLTP CO ₂ Emissions	Combined	(g/km)	88-95		
Fuel tank capacity - useable litres			58		

■ Standard

*When combined with electric motor. **The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route.

Engines

	PETROL PLUG-IN ELECTRIC HYBRID (PHEV)
BATTERY AND CHARGING TIMES	P270e
Home Charger / Wall box 7kW	2 hours 12 minutes to 100%
Rapid DC Charger 32kW	30 mins to 80%
Domestic Plug 2,3kW	6 hours 42 minutes to 100%
Battery capacity Total (Usable) kWh	15 (12,17)
Charging cable length (m)	5
PERFORMANCE	
Acceleration (secs) 0-100 km/h	7,4
Maximum speed km/h	190
ELECTRIC MOTOR DATA	
Maximum power PS (kW)	109 (80)
Maximum torque (Nm)	260
EV Range Combined (WLTP*) km	58-56
EV Range expected Real World data (up to) km	45
BRAKES	
Front type	Twin piston, sliding caliper, Vented discs
Front diameter (mm)	349
Rear type	Single piston, sliding caliper, Vented discs
Rear diameter (mm)	325
Park brake diameter (mm)	325
WEIGHTS (kg)**	
Seating	5
Unladen weight (EU)†	2.168
Unladen weight (DIN)††	2.093
Gross Vehicle Weight (GVW)	2.750
TOWING (kg)	
Seating	5
Unbraked trailer	750
Maximum towing	Up to 1.600
Maximum coupling point (nose weight)	100
Maximum vehicle and trailer combination	4.350
ROOF CARRYING (kg)	
Maximum roof load (including cross bars)‡	75

*The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂ , fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. **Weights reflect vehicles to standard specifications. Optional extras increase weight. †Includes a 75kg driver, full fluids and 90% fuel. ††Includes full fluids and 90% fuel. ‡Roof carrying load reduced to 60kg when Summer Tyres are fitted.

Engines

			DIESEL MILD HYBRID (MHEV)		
ENGINE			D165		D200
Mild Hybrid Electric Vehicle (MHEV)			■		■
Transmission			Automatic		Automatic
Driveline			All Wheel Drive (AWD)		All Wheel Drive (AWD)
Maximum power (PS / kW / rpm)			163 / 120 / 3.500-4.250		204 / 150 / 3.750
Maximum torque (Nm / rpm)			380 / 1.500-2.500		430 / 1.750-2.500
Capacity (cc)			1.998		1.998
No. of cylinders / Valves per cylinder			4 / 4		4 / 4
Cylinder layout			Inline		Inline
Bore / stroke (mm)			83,0 / 92,3		83,0 / 92,3
Compression ratio (:1)			16,5+ / -0,5		16,5+ / -0,5
FUEL ECONOMY – WLTP*					
Seating			5 / 5 + 2		5 / 5 + 2
WLTP Consumption	Low	l/100km	7,8-8,3 / 8,1-8,4**		7,8-8,5 / 8,1-8,4**
	Medium	l/100km	6,8-7,2 / 7,0-7,4		6,8-7,5 / 7,0-7,4
	High	l/100km	5,7-6,0 / 5,8-6,0		5,7-6,2 / 5,8-6,1
	Extra High	l/100km	6,7-7,0 / 6,8-7,1		6,7-7,2 / 6,8-7,1
	Combined	l/100km	6,5-6,9 / 6,7-7,0		6,5-7,1 / 6,7-7,0
WLTP CO ₂ Emissions	Low	(g/km)	205-217 / 212-221**		205-223 / 212-221**
	Medium	(g/km)	178-189 / 184-193		178-195 / 184-193
	High	(g/km)	149-156 / 152-158		149-161 / 152-159
	Extra High	(g/km)	174-183 / 177-186		174-189 / 177-186
	Combined	(g/km)	172-181 / 175-184		171-186 / 175-184

■ Standard.

*The figures provided are as a result of official manufacturer’s tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. **When Efficiency Pack fitted.

Engines

	DIESEL MILD HYBRID (MHEV)	
FUEL ECONOMY – CONTINUED	D165	D200
Fuel tank capacity - useable litres	65	65
Diesel Exhaust Fluid (DEF) - useable litres	17	17
PERFORMANCE		
Seating	5 / 5 + 2	5 / 5 + 2
Acceleration (secs) 0-100 km/h	10,2 / 10,6	8,6 / 8,9
Maximum speed km/h	195 / 193	209 / 209
BRAKES		
Front type	Single Piston, sliding caliper, Vented discs Twin piston, sliding caliper, Vented discs	Single Piston, sliding caliper, Vented discs Twin piston, sliding caliper, Vented discs
Front diameter (mm)	325 / 349	325 / 349
Rear type	Single piston, sliding caliper, Solid discs / Single piston, sliding caliper, Vented discs	Single piston, sliding caliper, Vented discs Single piston, sliding caliper, Solid discs / Single piston, sliding caliper, Vented discs
Rear diameter (mm)	300 / 325	325 / 300 / 325
Park brake diameter (mm)	300 / 325	325 / 300 / 325
WEIGHTS (kg)*		
Seating	5 / 5 + 2	5 / 5 + 2
Unladen weight (EU)**	1.949 / 2.028	1.949 / 2.028
Unladen weight (DIN)†	1.874 / 1.953	1.874 / 1.953
Gross Vehicle Weight (GVW)	2.590 / 2.750	2.590 / 2.750
TOWING (kg)		
Seating	5 / 5 + 2	5 / 5 + 2
Unbraked trailer	750	750
Maximum towing	Up to 2.200	Up to 2.500 / Up to 2.200
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.790 / 4.950	5.090 / 4.950
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)††	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. ††Roof carrying load reduced to 60kg when Summer Tyres are fitted.

ENGINES

ENGINE	DIESEL	
	D165	D200
Transmission	Automatic	Automatic
Driveline	All Wheel Drive (AWD)	All Wheel Drive (AWD)
Maximum power (PS / kW / rpm)	163 / 120 / 3.500-4.250	199 / 146 / 3.750-4.000
Maximum torque (Nm / rpm)	380 / 1.500-2.500	430 / 1.750-2.500
Capacity (cc)	1.998	1.998
No. of cylinders / Valves per cylinder	4 / 4	4 / 4
Cylinder layout	Inline	Inline
Bore / stroke (mm)	83,0 / 92,3	83,0 / 92,3
Compression ratio (:1)	16,5+ / -0,5	16,5+ / -0,5
PERFORMANCE		
Seating	5 / 5 + 2	5 / 5 + 2
Acceleration (secs) 0-100 km/h	10,2 / 10,6	8,6 / 8,9
Maximum speed km/h	195 / 195	209 / 209

ENGINES

	DIESEL	
BRAKES	D165	D200
Front type	Single Piston, sliding caliper, Vented discs Twin piston, sliding caliper, Vented discs	Single Piston, sliding caliper, Vented discs Twin piston, sliding caliper, Vented discs
Front diameter (mm)	325 / 349	325 / 249
Rear type	Single piston, sliding caliper, Solid discs / Single piston, sliding caliper, Vented discs	Single piston, sliding caliper, Vented discs Single piston, sliding caliper, Solid discs / Single piston, sliding caliper, Vented discs
Rear diameter (mm)	300 / 325	325 / 300 / 325
Park Brake	300 / 325	325 / 300 / 325
WEIGHTS (kg)*		
Seating	5 / 5 + 2	5 / 5 + 2
Gross Vehicle Weight (GVW)	2.590 / 2.750	2.590 / 2.750
TOWING (kg)		
Seating	5 / 5 + 2	5 / 5 + 2
Unbraked trailer	750	750
Maximum towing	Up to 2.200	Up to 2.200
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4.790 / 4.950	4.790 / 4.950
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)**	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Roof carrying load reduced to 60kg when Summer Tyres are fitted.

DIMENSIONS AND CAPABILITIES

DIMENSIONS
Maximum height 1.727mm
Overall length 4.597mm
Width 2.069mm mirrors folded
Width 2.173mm mirrors out
Front wheel track 1.625,2mm
Rear wheel track 1.631,3mm
Wheelbase 2.741mm
TURNING CIRCLE
Kerb-to-kerb 11,8m
Wall-to-wall 12,14m
Turns lock-to-lock 2,31

WADING DEPTH
Maximum wading depth 600mm
HEADROOM
Maximum front / rear headroom with standard roof 1.003mm / 984mm
Maximum front / rear headroom with panoramic roof 1.021mm / 984mm
LEGROOM
Maximum front legroom 993mm
Maximum rear legroom second row 968mm
Maximum rear legroom third row 665mm

LOADSPACE CAPACITY
Height 798mm, Width 1.323mm
Loadspace width between arches 1.107mm
Length behind first row 1.824mm
Length behind second row 967mm
5 seats
Maximum loadspace volume behind first row
Dry* 1.574 litres, Wet** 1.794 litres
Maximum loadspace volume behind second row
Dry* 963 litres, Wet** 1.179 litres
5 + 2 seats
Maximum loadspace volume behind first row
Dry* 1.451 litres, Wet** 1.651 litres
Maximum loadspace volume behind second row
Dry* 840 litres, Wet** 1.046 litres
Maximum loadspace volume behind third row
Dry* 115 litres, Wet** 157 litres

OBSTACLE CLEARANCE
Standard ride height 210mm
APPROACH AND DEPARTURE CLEARANCE
Approach Angle - 24,9°†
Departure Angle - 28,3°
Ramp Angle - 20,4°††



Maximum height 1.727mm

Width 2.069mm mirrors folded
Width 2.173mm mirrors out



Overall length 4.597mm



Rear wheel track 1.631,3mm

Weights and dimensions shown apply to standard-specification, unladen vehicles, which may be affected by optional features and equipment.

*Dry: volume as measured with Verband Der Automobilindustrie-compliant solid blocks (200mm x 50mm x 100mm). **Wet: volume as measured by simulating the loadspace filled with liquid. Figures are representative of seats fully forward and not tilted. †Approach Angle for P270e and P300e will be 25,0°. Fitting of side tubes or side steps may affect the off-road capability of the vehicle. Challenging off-road driving requires full training and experience. ††Ramp Angle for P270e and P300e will be 19.9°. Fitting of side tubes or side steps may affect the off-road capability of the vehicle. Challenging off-road driving requires full training and experience.

Vehicle shown is a Landmark in Varesine Blue (features fitted market dependent).